

## Polygomma™ Seam Tape Technical Data Sheet

The Polygomma Seam Tape is a self-adhesive tape manufactured from a high quality rubber compound, and is self-protected by a double sided release paper. The Polygomma Seam Tape is used to overlap the field joints of the Polygomma EPDM Roofing/Waterproofing Membrane and the Polygomma EPDM Pond Liners.

### Suggested Installation Guide

- The overlap surfaces, on the bottom and the top EPDM membrane/liner, should be clean, dry, smooth and dust-free.
- Clean the overlap areas with toluene, and wait for it to dry.
- Unroll the tape till the desired length is reached.
- Remove the release paper, and let the overlap area of the upper membrane fall on the seam tape.
- Press the overlap with a roller to achieve a secured overlap joint/seam.

For detailed installation procedure, please contact the supplier.

### Storage

The Seam Tapes must be stored in a cool, clean and dry premise, at or below 25°C. The shelf life of the material is 12 months.

### Physical Characteristics

- Excellent adhesion properties.
- Resistance to heat and cold.
- Resistance to UV and ageing.
- Solvent free.

### Characteristics (When Packed)

Base Material	Rubber Polymer
Colour	Black
Solids	100%
Application Temperature	0°C to 45°C
Service Temperature	0°C to 100°C

## Dimensions and Packaging

**Standard Length:** 30 meters

**Standard Width:** 75 mm

The rolls are packed in corrugated boxes. Specific widths may be available upon request.

## Safety and Precautions

The material is not hazardous for general uses. Keep out of reach of children. Possible handling risks, cuts and abrasions in particular conditions.

The information given here in is based on tests conducted in-house laboratory and/or independent accredited laboratories. While the information is presented as true and accurate to the best of our knowledge, Polygomma assumes no responsibility or liability with regard to the use of this information. The right to make periodic revisions of the specifications without prior notice is reserved. Many factors beyond our control can affect and influence the use and performance of our products at any particular application. Since these factors are uniquely within the users' knowledge and control, it is essential that users evaluate the product to determine its suitability for purpose. Please, ensure before using that product is suitable for the material intend application. No warranty is given or implied by us as the site conditions and the skill of labour used for application is beyond our control